GYP GRIP 40

Heavy Duty Construction Adhesive

Technical Data Sheet

Product Features
Meets ASTM-C557
Reduces Fastener Use up to 50%
Quick Grab Chemistry
Minimizes Nail Pops
Dampens Sound
Freeze Thaw Stable
Helps Build a Better Wall in Less Time

Product Description:

Gyp Grip 40 is a premier acrylic based construction adhesive formulated for adhering drywall to wood and steel studs, gypsum board to gypsum board, and bonding and securing various other building material substrates. Gyp Grip 40 offers fast grab for easy drywall installation and high strength adhesion that reduces nailing and the use of mechanical fasteners by up to 50%.

Standards & Specifications:

Tested to and Exceeds ASTM-C557 Performance Criteria
Standard Specification for Adhesives for Fastening Gypsum Wallboard to Wood Framing

EcoSeal Standards:
V.O.C. Content: **30 g/l**

Physical Properties:	
Chemistry	Acrylic Emulsion
Cure Type	Water Based
Color	Tan
Shelf Life	18 Months
Tack Free Time	10 Minutes at 75°F
Repositioning Time	15 Minutes
Application Temperature	40°F to 110°F
Water Resistance	Good
Freeze Thaw	5 Cycles
V.O.C. Level	30 grams / liter

Performance Specifications:	
Shear Strength	24 Hrs at Standard Conditions: 68 14 Days at Standard Conditions: 102
Bond Separation	40 lbs for 24 Hrs at Standard Conditions: None 20 lbs for 24 Hrs at 100°F: None
Tensile Strength	24 Hrs. at Standard Conditions: 16 14 Days at Standard Conditions: 28
Open Time	24 Hrs at Standard Conditions Paper Transfer: >95%
Bridging	48 Hrs at Standard Conditions Percent Paper Faliure: >95%
Accelerated Aging	500 Hrs at 158°F Cracking: None

EverKem Diversified Products
5180 Indiana Avenue Winston Salem, 27106
PH: 1.800.638.3160 / FX: 1.336.661.7969
www.everkemproducts.com

GYP GRIP 40

Heavy Duty Construction Adhesive

Technical Data Sheet

Applications:

- Wood studs
- Steel studs
- Rafters
- Drywall
- Concrete

NOT Recommended For:

- Exterior wall construction
- Extruded polystyrene foam
- Polystyrene of ABS plastic panels
- Ceiling tiles and acoustical panels

Application Procedures:

Installing Drywall to Wood and Metal Studs:

1. Cut and pre-fit drywall prior to application of adhesive.
2. Apply a continuous 3/8" bead of adhesive directly to studs and plates starting approximately 5 inches from the top and bottom of where each drywall panel is positioned on the stud and plates.
3. Apply two additional parallel ¼" beads of adhesive on the stud at the joint where two drywall pieces meet.
4. Position drywall and press firmly to the stud.
5. Follow the fastening table R702.3.5 for drywall applications using an adhesive as stated by 2012 IRC and/or the fastening requirements as stated in the Gypsum Association Manual (GA-216).
6. For best results, boards should not be finished until adhesive has fully cured.

Clean Up Procedures:

Excess caulk should be cleaned off tools and nonporous surfaces while it is in the uncured state using soap, water, and a dry cloth or paper towel. Cured compound should be cut away

Packaging Options:

Part #	Product Description	Color	Case Quantity
GG40-28	Gyp Grip 40 Heavy Duty Construction Drywall Adhesive - 28 Fl. Oz. Tube	Tan	12 tubes/case
GG40-28	Gyp Grip 40 Heavy Duty Construction Drywall Adhesive - 28 Fl. Oz. Sausage Tube	Tan	16 tubes/case

CAUTION: May cause skin, eye, and respiratory irritation. Avoid contact with eyes and skin. Use with adequate ventilation. Do not swallow. FIRST AID: If swallowed, do not induce vomiting. Call a physician or Poison Control center. For eye contact, flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water. If affected by vapors, get fresh air. KEEP OUT OF REACH OF CHILDREN.WARNING: This product contains chemicals known to the State of California to cause cancer.

Scan this QR Code to be directed to our online product page, where you can view additional information including Safety Data Sheets and Applicable Testing Documentation

Disclaimer:

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

EverKem Diversified Products
5180 Indiana Avenue Winston Salem, 27106
PH: 1.800.638.3160 / FX: 1.336.661.7969
www.everkemproducts.com